Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878



Issue date: 28/02/2025 Revision date: 28/02/2025 Supersedes version of: 28/02/2025 Version: 1.0

SECTION 1: Identification of the substa	nce/mixture and of the company/undertaking
1.1. Product identifier	
Product form Trade name UFI Type of product Product group	 Mixture DELTA®- THENE GRUNDANSTRICH 3330-D0MA-V00T-NJ24 Paint,Solvent-based primers, pigmented Trade product
1.2. Relevant identified uses of the substance	ce or mixture and uses advised against
Relevant identified uses Main use category Industrial/Professional use spec Use of the substance/mixture Function or use category	 Professional use For professional use only Solvent-based primers, pigmented 55/999 Others
1.3. Details of the supplier of the safety data	a sheet
Supplier DÖRKEN GmbH & Co.KG Wetterstraße 58 DE 58313 Herdecke Deutschland T 0049 (0)2330/ 63-0 msds@doerken.de, www.doerken.de 1.4. Emergency telephone number	
Emergency number	: ChemTrec: 0800-181-7059 24 hours
SECTION 2: Hazards identification	
2.1. Classification of the substance or mixtu	ıre
Classification according to Regulation (EC) No. 12	272/2008 [CLP]
Flammable liquids, Category 3 Skin sensitisation, Category 1 Specific target organ toxicity – Single exposure, Cate Narcosis Aspiration hazard, Category 1 Full text of H- and EUH-statements: see section 16	H226 H317 egory 3, H336 H304
Adverse physicochemical, human health and env	ironmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	
	GHS02 GHS07 GHS08
Signal word (CLP)	: Danger
Contains	 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, 2% aromatics;rosin; colophony
Hazard statements (CLP)	 H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area.
EUH-statements Extra phrases	 EUH066 - Repeated exposure may cause skin dryness or cracking. Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bitumen 50/70 substance with national workplace exposure limit(s) (BE, EE, ES, GB, GR, HR, IE, PL, PT, RO, NO, MK, CH)	CAS-No.: 8052-42-4 EC-No.: 232-490-9 REACH-no: 01-2119480172- 44	50 - 60	Not classified
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclenes, <2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258- 33	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
xylene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	1 - < 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
rosin; colophony substance with national workplace exposure limit(s) (CZ, GB, HR, LV, RO)	CAS-No.: 8050-09-7 EC-No.: 232-475-7 EC Index-No.: 650-015-00-7 REACH-no: 01-2119480418- 32	1- < 5	Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=2.3 mg/l/4h) Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.
4.2. Most important symptoms and e	ffects, both acute and delayed
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Flammable liquid and vapour. No direct explosion hazard. Toxic fumes may be released.
5.3. Advice for firefighters	
Firefighting instructions Protection during firefighting	 Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 6: Accidental release r	neasures
6.1. Personal precautions, protective	e equipment and emergency procedures
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
For non-emergency personnel	
Protective equipment Emergency procedures	 Wear recommended personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures 6.2. Environmental precautions	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Avoid release to the environment.	
6.3. Methods and material for contain	inment and cleaning up
For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13	

For further information refer to section 13.

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed Precautions for safe handling	 Not expected to present a significant hazard under anticipated conditions of normal use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. 		
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including a	any incompatibilities		
Technical measures Storage conditions Packaging materials	 Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store always product in container of same material as original container. 		

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Bitumen 50/70 (8052-42-4)			
United Kingdom - Occupational Exposure Limits			
Local name	Asphalt		
WEL TWA (OEL TWA)	5 mg/m ³ petroleum fumes		
WEL STEL (OEL STEL)	10 mg/m ³ petroleum fumes		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
rosin; colophony (8050-09-7)			
United Kingdom - Occupational Exposure Limi	ts		
Local name	Rosin-based solder flux fume		
WEL TWA (OEL TWA)	0.05 mg/m³		
WEL STEL (OEL STEL)	0.15 mg/m³		
Remark	Sen (Capable of causing occupational asthma)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
xylene (1330-20-7)			
EU - Indicative Occupational Exposure Limit (I	DEL)		
Local name	Xylene, mixed isomers, pure		
IOEL TWA	221 mg/m ³		
	50 ppm		
IOEL STEL	442 mg/m ³		
	100 ppm		
Remark	Skin		
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC		
United Kingdom - Occupational Exposure Limi	ts		
Local name	Xylene		
WEL TWA (OEL TWA)	220 mg/m ³ o-,m-,p- or mixed isomers		
	50 ppm o-,m-,p- or mixed isomers		
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers		
	100 ppm o-,m-,p- or mixed isomers		
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
United Kingdom - Biological limit values			
Local name	Xylene, o-, m-, p- or mixed isomers		
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
	· · ·		

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment. Use eye protection according to EN 166. Butyl-rubber protective gloves. Impermeable clothing. **Personal protective equipment symbol(s):**



Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety goggles	Droplet	With side shields, Plastic	EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection			
Туре			
Chemically resistant protective gloves	EN 174		
Impermeable clothing			
Apply emollient cream			

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Butyl rubber	6 (> 480 minutes)	0,7 mm		EN 374-2, EN 374-3

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Full face mask	ABEK	If conc. in air > exposure limit	EN 14387

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Blue.
Appearance	:	Pasty liquid.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Not self-igniting, Flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	:
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: 7.5 – 8.5
Viscosity, kinematic	: Not available
Solubility	: In water, material soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1 – 1.05 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content

: 24.6 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)	
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)	
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)	
Bitumen 50/70 (8052-42-4)		
LD50 oral rat	≥ 5000 mg/kg Source: ECHA	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Bitumen 50/70 (8052-42-4)	
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 94.4 mg/m ³ Source: ECHA
rosin; colophony (8050-09-7)	
LD50 oral rat	7800 mg/kg Source: IUCLID
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	2500 mg/kg
LC50 Inhalation - Rat	2.3 mg/l
xylene (1330-20-7)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
Skin corrosion/irritation :	Not classified (Based on available data, the classification criteria are not met) pH: 7.5 – 8.5
Serious eye damage/irritation :	Not classified (Based on available data, the classification criteria are not met) pH: 7.5 – 8.5
Respiratory or skin sensitisation :	May cause an allergic skin reaction.
Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity :	Not classified (Based on available data, the classification criteria are not met)
Bitumen 50/70 (8052-42-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity :	Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure :	May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, n-alkanes, isoalkane <2% aromatics	s, cyclenes,
STOT-single exposure	May cause drowsiness or dizziness.
xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	Not classified (Based on available data, the classification criteria are not met)
Bitumen 50/70 (8052-42-4)	
LOAEL (dermal, rat/rabbit, 90 days)	200 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard :	May be fatal if swallowed and enters airways.
11.2. Information on other hazards	

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

according to Regulation (EC) No. 1907/2006 (REACH) wi	th its amendment Regulation (EU) 2020/878
Hazardous to the aquatic environment, short-term (acute)	
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)
rosin; colophony (8050-09-7)	
LC50 - Fish [1]	5.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	5.4 mg/l Test organisms (species):
EC50 - Crustacea [1]	4.5 mg/l
xylene (1330-20-7)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
12.2. Persistence and degradability	
DELTA®- THENE GRUNDANSTRICH	
Persistence and degradability	Not rapidly degradable
Bitumen 50/70 (8052-42-4)	
Persistence and degradability	Not rapidly degradable
Hydrocarbons, C9-C11, n-alkanes, isoalk <2% aromatics	anes, cyclenes,
Persistence and degradability	Not rapidly degradable
rosin; colophony (8050-09-7)	
Persistence and degradability	Not rapidly degradable
xylene (1330-20-7)	
Persistence and degradability	Not rapidly degradable
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessme	nt
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	S
13.1. Waste treatment methods	

13.1. Waste treatment methods

Regional waste regulation

: Disposal must be done according to official regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Waste treatment methods Sewage disposal recommendations Product/Packaging disposal recommendations Additional information HP Code	 Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal must be done according to official regulations. Disposal must be done according to official regulations. Flammable vapours may accumulate in the container. Do not re-use empty containers. HP3 - "Flammable:"
	 flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; water reactive waste: waste which, in contact with water, emits flammable gases in

dangerous quantities;

- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID r	humber	1		l
UN 1139	UN 1139	UN 1139	UN 1139	UN 1139
14.2. UN proper shippin	ig name	11		1
COATING SOLUTION	COATING SOLUTION	Coating solution	COATING SOLUTION	COATING SOLUTION
Transport document descu	ription	11		1
UN 1139 COATING SOLUTION, 3, III, (D/E)	UN 1139 COATING SOLUTION, 3, III	UN 1139 Coating solution, 3, III	UN 1139 COATING SOLUTION, 3, III	UN 1139 COATING SOLUTION, 3, III
14.3. Transport hazard	class(es)			
3	3	3	3	3
14.4. Packing group				
III	III	III	III	
14.5. Environmental haz	zards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	n available			
14.6. Special precaution	s for user			
Overland transport				
Classification code (ADR) Limited quantities (ADR)	: F1 : 5l			

: E1

: P001, IBC03, LP01, R001

```
: MP19
```

Excepted quantities (ADR)

Packing instructions (ADR)

Mixed packing provisions (ADR)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions	: TP1
(ADR)	
	: LGBF
Tank code (ADR)	
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	20
	30
	1120
	1139
Turne al manteistic manufa (ADD)	
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y
Transport by sea	
Special provisions (IMDG)	: 955
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
	: A
Stowage category (IMDG)	
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.
Air transport	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L
Inland waterway transport	
	. 54
Classification code (ADN)	: F1
Limited quantities (ADN)	: 5L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0
Rail transport	
Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
-	: MP19
Mixed packing provisions (RID)	
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions	: TP1
(RID)	
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content

: 24.6 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
American Conference of Government Industrial Hygienists		
European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
European Agreement concerning the International Carriage of Dangerous Goods by Road		
Acute Toxicity Estimate		
Bioconcentration factor		
Biological limit value		
Biochemical oxygen demand (BOD)		
Chemical Abstract Service number		
Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and ac	ronyms:
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
МАК	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Flam. Liq. 3	Flammable liquids, Category 3	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.