Page 1/12



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

### Trade name: LUCITE® 806 RoofCoat

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

#### Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

#### **1.4 Emergency telephone number:**

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. **Hazard pictograms** 



Signal word Warning

(Contd. on page 2)

Page 2/12



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

## Trade name: LUCITE® 806 RoofCoat

	(Contd.	of page 1)
Hazard-determi	ining components of labelling:	
2-octyl-2H-isothi	iazol-3-one	
2-methyl-2H-isot	othiazol-3-one	
mixture of: 5-chl	loro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	
1,2-benzisothiaz	zol-3(2H)-one	
diuron		
Hazard stateme	ents	
H317 May cause	e an allergic skin reaction.	
H412 Harmful to	o aquatic life with long lasting effects.	
<b>Precautionary</b> s	statements	
P273 Avo	pid release to the environment.	
P280 Wea	ear protective gloves.	
P302+P352 IF C	ON SKIN: Wash with plenty of soap and water.	
P362+P364 Tak	ce off contaminated clothing and wash it before reuse.	
P501 Disp	pose of contents/container in accordance with local/regional/national/international regu	ulations.
Additional infor	rmation:	
EUH211 Warnin	ng! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray	y or
mist.		
2.3 Other hazar	rds	
	and vPvB assessment	
PBT: Not applica		
vPvB: Not applie		

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5	Carc. 2, H351	
Reg.nr.: 01-2119489379-17-xxxx		
CAS: 77-99-6	propylidynetrimethanol	<0.25%
EINECS: 201-074-9	Repr. 2, H361fd	
Reg.nr.: 01-2119486799-10-xxxx		

Page 3/12



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

## Trade name: LUCITE® 806 RoofCoat

CAS: 220 E4 1	diuron	(Contd. of page
CAS: 330-54-1	diuron	≥0.025-<0.1%
EINECS: 206-354-4	Carc. 2, H351; STOT RE 2, H373; Aquatic Acute 1,	
Reg.nr.: 01-2119517622-45-xxxx		
	Acute Tox. 4, H302	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	≥0.025-<0.1%
EINECS: 247-761-7	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute	
	Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1,	
	H318; Aquatic Acute 1, H400 (M=100); Aquatic	
	Chronic 1, H410 (M=100); Skin Sens. 1A, H317,	
	EUH071	
	ATE: LD₅₀ oral: 125 mg/kg	
	$LD_{50}$ dermal: 311 mg/kg	
	$LC_{50}$ / 4 h inhalative: 0.27 mg/l	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C≥ 0.0015 %	
040,0004,005		00.0050
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	≥0-<0.025%
EINECS: 220-120-9	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic	
Reg.nr.: 01-2120761540-60-xxxx		
	Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1,	
	H317	
	Specific concentration limit:	
	Skin Sens. 1; H317: C≥ 0.05 %	
CAS: 2682-20-4	2-methyl-2H-isothiazol-3-one	≥0.0015-<0.025%
EINECS: 220-239-6	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute	
Reg.nr.: 01-2120764690-50-xxxx		
0	H318; Aquatic Acute 1, H400 (M=10); Aquatic	
	Chronic 1, H410 (M=1); Skin Sens. 1A, H317,	
	EUH071	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C≥ 0.0015 %	
CAS: 55965-84-9	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one	
	5	≥0.00025-<0.0015
rey.111 01-2120/04091-48-XXXX	and 2-methyl-2H-isothiazol-3-one (3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute	
	Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1,	
	H318; Aquatic Acute 1, H400 (M=100); Aquatic	
	Chronic 1, H410 (M=100); Skin Sens. 1A, H317,	
	EUH071	
	Specific concentration limits:	
	Skin Corr. 1C; H314:C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: 0.06 % $\leq$ C < 0.6 %	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

(Contd. of page 3)

#### Trade name: LUCITE® 806 RoofCoat

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

#### After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

#### After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

#### After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

#### **4.3 Indication of any immediate medical attention and special treatment needed** Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

## 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

(Contd. on page 5)

Page 5/12

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

(Contd. of page 4)

## Trade name: LUCITE® 806 RoofCoat

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes.

#### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Keep contaminated washing water and dispose of appropriately.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

# 7.2 Conditions for safe storage, including any incompatibilities Storage:

#### Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

#### Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

#### Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

(Contd. on page 6)

DE/EN





according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

### Trade name: LUCITE® 806 RoofCoat

(Contd. of page 5)

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

#### 57-55-6 Propylene glycol

MAK (Germany) als Dampf und Aerosol;vgl.Abschn.Ilb und Xc

55965-84-9 mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

#### MAK (Germany) | Long-term value: 0.2E mg/m<sup>3</sup>

vgl.Abschn.Xc

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

#### Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

### Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

#### **Respiratory protection:**

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

#### Hand protection

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

#### Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye/face protection

Wear protective goggles to protect against splashing. Have eye wash bottle or eye rinse ready at work place. Professional Cooperative Rules - BGR 192 Use of eye and face protection

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 01.03.2024 Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

(Contd. of page 6)

## Trade name: LUCITE® 806 RoofCoat

Body protection: Impervious protective clothing

9.1 Information on basic physical and chemical	properties
General Information	highering
Physical state	Fluid
Colour:	Different according to colouring
Odour:	Ammonia-like
Odour threshold:	For mixtures not applicable.
Melting point/Freezing point:	Not security-related.
Boiling point or initial boiling point and boiling	not obtainly related.
range	100 °C (7732-18-5 water)
Flammability	Not applicable.
Lower and upper explosion limit	1. F
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Not applicable.
Decomposition temperature:	For mixtures not applicable.
pH at 20 °C	8.5-9.5
Viscosity:	Not security-related.
Solubility	····· <b>·</b> ······························
water:	Miscible / waterdilutable.
polar solvents:	Partly miscible.
non-polar solvents:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	For mixtures not applicable.
Vapour pressure at 20 °C:	23 hPa (7732-18-5 water)
Density and/or relative density	, ,
Density at 20 °C:	1.23-1.43 g/cm³
Vapour density	Not applicable.
9.2 Other information	•
Appearance:	
Form:	Fluid
Important information on protection of health a	
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not senigriting. Product does not present an explosion hazard.
Change in condition	r rouder does not present an explosion nazard.
Softening point/range	
Oxidising properties	In its condition as supplied, the product is neither
Oxidiality higherites	flammable nor oxidising.



according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

### Trade name: LUCITE® 806 RoofCoat

Evaporation rate	For mixtures not applicable.	
Information with regard to physical hazard		
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

#### **SECTION 10: Stability and reactivity**

10.1 Reactivity No further relevant information available.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:** 

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met. LD/LC50 values relevant for classification: No further relevant information available.

#### Skin corrosion/irritation

May cause irritations.

(Contd. on page 9)

Page 9/12

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

(Contd. of page 8)

List II

**DÖRKEN<sup>®</sup>** 

## Trade name: LUCITE® 806 RoofCoat

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

May cause irritations. Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** May cause an allergic skin reaction. **Germ cell mutagenicity** Based on available data, the classification criteria are not met. **Carcinogenicity** Based on available data, the classification criteria are not met. **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

#### Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard. Based on available data, the classification criteria are not met.

#### Additional toxicological information:

#### CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

#### **Endocrine disrupting properties**

330-54-1 diuron

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

## 12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

## 12.7 Other adverse effects

### Other information:

This product contains the following priority substance in accordance with Annex X of the EU Water Directive 2000/60/EC:

330-54-1 Diuron



according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

### Trade name: LUCITE® 806 RoofCoat

(Contd. of page 9)

General notes: Do not allow product to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

#### European waste catalogue

08 01 11<sup>\*</sup> waste paint and varnish containing organic solvents or other hazardous substances HP14 Ecotoxic

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according to IMO Instruments Not applicable.		
UN "Model Regulation":	Void	

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)

- DE/EN -

Page 11/12



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

### Trade name: LUCITE® 806 RoofCoat

(Contd. of page 10)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (WB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012 Additional information:

Contains protective agent for products in storage and coating protective agent. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

Page 12/12



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.03.2024

Version number 01-01 (replaces version 01-00)

Revision: 01.03.2024

## Trade name: LUCITE® 806 RoofCoat

11040		(Contd. of page 1
H310	Fatal in contact with skin.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H351	Suspected of causing cancer.	
H361fd	Suspected of damaging fertility. Suspected	
H373	May cause damage to organs through prolo	nged or repeated exposure.
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting eff	ects.
EUH071	Corrosive to the respiratory tract.	
Classifi	cation according to Regulation (EC) No 12	272/2008
Skin ser	nsitisation	The classification of the mixture is generally based or
		the calculation method using substance data
		according to Regulation (EC) No 1272/2008.
Hazardo	ous to the aquatic environment - long-term	Expert judgement
	) aquatic hazard	
Date of	previous version: 03.01.2024	1
	number of previous version: 01-00	
	ations and acronyms:	
	. 3: Acute toxicity – Category 3	
	4: Acute toxicity – Category 4	
Acute Tox	. 2: Acute toxicity – Category 2	
	1: Skin corrosion/irritation – Category 1	
	1B: Skin corrosion/irritation – Category 1B	
	1C: Skin corrosion/irritation – Category 1C 2: Skin corrosion/irritation – Category 2	
	1: Serious eye damage/eye irritation – Category 2	
	1: Skin sensitisation – Category 1	
	. 1A: Skin sensitisation – Category 1A	
	arcinogenicity – Category 2	
	eproductive toxicity – Category 2	
	2: Specific target organ toxicity (repeated exposure) – (	
	cute 1: Hazardous to the aquatic environment - acute ac hronic 1: Hazardous to the aquatic environment - long-te	
	hronic 3: Hazardous to the aquatic environment - long-te	
	ompared to the previous version altered.	
	· · · · · · · · · · · · · · · · · · ·	DE